

FICHA TÉCNICA

CERAMICA 60X120 CM
ERMITAGE SATUARIO GREY



SUCERAMICA®

Inspírate y haz realidad tus ideas

SUCERAMICA DEL CARIBE & CIA S.A.S

NIT: 900324817-6

CARECTERISTICA TECNICAS:

CERAMICO		TIPO DE SUPERFICIE	RIBETE	RECOMENDACIONES DE USO	TRAFICO	PESO DEL PRODUCTO	PEI	M2/CAJA	PIEZAS/CAJA	ANTIDESLIZANTE	VARIACIÓN LIGERA
SERIE	REFERENCIA										
SATUARIO	ERMITAGE	PULIDO	RECTIFICADO	INTERIORES/ EXTERIORES	RESIDENCIAL			1,44 M2	2	NO	

TECHNICAL SPECIFICATIONS - GLAZED VITRIFIED TILES (GROUP BIa)

CHARACTERISTIC	TEST METHOD	INTERNATIONAL STD ISO 13006/EN 176 GROUP BIa	OUR VALUE
DIMENSION & SURFACE QUALITY			
Deviation In Length	ISO-10545-2	±0.6%	±0.2%
Deviation In Thickness	ISO-10545-2	±5%	±4%
Straightness of Sides	ISO-10545-2	±0.5%	±0.2%
Rectangularity	ISO-10545-2	±0.6%	±0.2%
Surface Flatness	ISO-10545-2	±0.5%	±0.2%
PHYSICAL & THERMAL PROPERTIES			
Water Absorption	ISO-10545-3	<0.5%	<0.2%
Mohs Hardness	EN-101	Min.3	Min.3
Flexural Strength	ISO-10545-4	>35 N/mm2	>40N/mm2
Skid Resistance (Friction Coefficient)	ISO-10545-17	-	<0.2 (R9)
Breaking Strength	ISO-10545-11	>1113 N	>1800N
Frost Resistance	ISO-10545-12	Frost Proof	Frost Proof
Thermal Shock Resistance	ISO-10545-9	No Damage	No Damage
Moisture Expansion	ISO-10545-10	NIL	NIL
Resistance to Surface Abrasion	ISO-10545-7	-	PEI III & IV
CHEMICAL PROPERTIES			
Chemical Resistance	ISO-10545-13	No Damage	No Damage
Color Resistance	ISO-10545-16	No Damage	No Damage
Stain Resistance	ISO-10545-14	Resistant	Resistant