

FICHA TÉCNICA

PORCELANATO MUSTARD 60X120

CARECTERISTICA TECNICAS:

CERAMICO		TIPO DE SUPERFICIE	RIBETE	RECOMENDACIONES DE USO	TRAFICO	PESO DEL PRODUCTO	ESPESOR	M2/CAJA	PIEZAS/CAJA	ANTIDESLIZANTE
SERIE	REFERENCIA									
MUSTAR	SILVER, SMOKE, CREMA	MATE	RECTIFICADO	INTERIORES	COMERCIAL	APROX. 28KG	10 MM	1,44 M2	02	NO

DECLARATION OF PERFORMANCE

Dear Sir/Madam,
Please Find Below Prodcut Perfomance.

PRODUCT : GLAZED PORCELAIN TILES
H.S CODE: 69072100

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN14411 GROUP Bla	OUR VALUE	TEST METHOD
Deviation in length & width	± 0.6%	± 0.2%	ISO-10545-2
Deviation in thickness	± 5.0%	± 3.0%	ISO-10545-2
Straightness in side	± 0.5%	± 0.2%	ISO-10545-2
Rectangularity	± 0.5%	± 0.2%	ISO-10545-2
Surface flatness	± 0.5%	± 0.2%	ISO-10545-2
Water absorption	< 0.50%	< 0.05%	ISO-10545-3
Modulus of repture	Min. 35 N/mm2	Min. 40 N/mm2	ISO-10545-4
Breaking strength	>1113N	>1 00N	ISO-10545-4
MOH's hardness	Min.5	Min. 5	EN 101
Frost resistance	Frost Proof	Frost Proof	ISO-10545-12
Thermal shock resistance	No damage	No damage	ISO-10545-9
Moisture expansion	Nill	Nill	ISO-10545-10
Chemical resistance	No damage	No damage	ISO-10545-13
Stain resistance	Resistant	Resistant	ISO-10545-14
Color resistance	No damage	No damage	ISO-10545-16